



스틸 옥외 CT계량기함(1.6T)

모델	가로(W)	세로(H)	깊이(D)
CT-1	600	800	250



스텐 옥외 3상 계량기함(STS 201, 1.2T)

모델	가로(W)	세로(H)	깊이(D)
SCT-1	350	420	200



스틸 옥외 CT 2도어 계량기함(1.6T)

모델	가로(W)	세로(H)	깊이(D)
CT-2	600	1100	250



스텐 옥외 CT 2도어계량기함(STS 201, 1.2T)

모델	가로(W)	세로(H)	깊이(D)	전용
SCT-1	600	1100	250	200AF
SCT-2	800	1400	250	400AF <span style="color:red">신제품</span>



스텐 옥외 SCT 단상 계량기(STS 201, 1.2T)

모델	가로(W)	세로(H)	깊이(D)
1회로	250	600	150
2회로	400	600	150



스텐 옥외 SCT 3상 계량기(STS 201, 1.2T)

모델	가로(W)	세로(H)	깊이(D)
1회로	350	700	150
2회로	550	700	150
3회로	750	700	150



## 전기차 계량기함

### SUS 201 1.2T 계량기함

- ◎ 옥외 방수 단상 계량기함(고무패킹포함)
- ◎ 2P 5KA 차단기 및 접지 포함(ELB)
- ◎ SUS 재고 보유
- ◎ 명판포함
- ◎ 외함만 구매 가능(가격문의)

### 세트가격

모델	가로(W)	세로(H)	깊이(D)
SUS 201/1.2T	250	600	130
차단기 제외	250	600	130



스텐 옥외 SCT 단상 계량기(STS 201, 1.2T)

모델	가로(W)	세로(H)	깊이(D)
분전반 WHM	400	800	150

\*계량기 공간 300



스텐 옥외 SCT 3상 계량기(STS 201, 1.2T)

모델	가로(W)	세로(H)	깊이(D)
분전반 WHM	600	1000	150

\*계량기 공간 400




### HDS 스틸 옥내 노출 분전함(스틸 1.6T)

(단위 : mm)

모델	가로(W)	세로(H)	깊이(D)
1	300	400	150
2	400	500	150
3	400	500	200
4	500	500	150
5	500	600	150
6	500	600	200
7	500	700	150
8	500	700	200
9	500	800	150
10	500	900	150
11	550	600	150
12	600	600	150
13	600	700	150
14	600	700	200
15	600	800	150
16	600	800	200
17	600	900	150
18	600	900	200
19	600	1000	150
20	600	1000	200
21	600	1200	150
22	600	1200	200
23	700	800	150
24	700	900	150
25	700	900	200

모델	가로(W)	세로(H)	깊이(D)
26	700	1000	150
27	700	1000	200
28	700	1200	150
29	700	1200	200
30	700	1300	200
31	700	1400	200
32	700	1500	200
33	700	1600	200
34	700	1800	250
35	800	900	150
36	800	900	200
37	800	1000	150
38	800	1000	200
39	800	1200	250
40	800	1400	250
41	800	1500	250
42	800	1800	250
43	900	1600	250
44	900	1800	250
옥내자립(베이스 높이 200mm)포함 (45-48)			
45	900	1800(200)	400
46	800	2200(200)	400
47	900	2200(200)	400
48	1000	2200(200)	400



### HS(매입함) STEEL 1.6T

(단위 : mm)

모델	가로(W)	세로(H)	깊이(D)
1	300	400	150
2	400	400	150
3	400	500	150
4	500	500	150
5	500	600	150
6	500	700	150
7	500	800	150
8	550	600	150
9	600	600	150
10	600	700	150
11	600	800	150
12	600	900	150
13	600	1000	150
14	600	1200	150
15	700	800	150
16	700	900	150
17	700	1000	150
18	700	1200	150
19	800	900	150
20	800	1000	150
21	800	1200	150
22	800	1400	150

### SS(스텐도어) STS 201-1.2T

(단위 : mm)

모델	가로(W)	세로(H)
1	300	400
2	400	400
3	400	500
4	500	500
5	500	600
6	500	700
7	500	800
8	550	600
9	600	600
10	600	700
11	600	800
12	600	900
13	600	1000
14	600	1200
15	700	800
16	700	900
17	700	1000
18	700	1200
19	800	900
20	800	1000
21	800	1200
22	800	1400



### HB(컨트롤박스) STEEL 1.0T

(단위 : mm)

모델	가로(W)	세로(H)	깊이(D)
1	300	400	150
2	400	500	150
3	400	500	200
4	500	600	150
5	500	600	200
6	600	600	150
7	600	700	150
8	600	700	200
9	600	800	150
10	600	800	200
11	600	900	150
12	600	900	200
13	600	1000	150
14	700	800	150
15	700	900	150

### HT 옥외 방수노출형 STEEL 1.6T



(단위 : mm)

모델	가로(W)	세로(H)	깊이(D)
1	300	400	150
2	400	500	150
3	400	500	200
4	500	600	150
5	500	600	200
6	500	700	150
7	500	700	200
8	600	600	150
9	600	700	150
10	600	700	200
11	600	800	150
12	600	800	200
13	600	900	150
14	600	900	200
15	700	800	200
16	700	900	200
17	700	1000	200
18	700	1200	200
19	800	1200	200
20	800	1200	250
No.21번 VM, AM, AS, VS 타공포함, 베이스 포함			
21	900	2200(200)	400



### SHDS 스텐레스 옥내 분전함(SUS 201)

(단위 : mm)

모델	가로(W)	세로(H)	깊이(D)
1	300	400	150
2	300	400	200
3	400	500	150
4	400	500	200
5	500	600	150
6	500	600	200
7	500	700	150
8	500	700	200
9	600	700	150
10	600	700	200
11	600	800	150
12	600	800	200
13	600	900	150
14	600	900	200
15	600	1,000	150
16	600	1,000	200
17	600	1,200	150
18	600	1,200	200
19	700	800	150
20	700	800	200
21	700	900	150
22	700	900	200
23	700	1,000	150
24	700	1,000	200
25	700	1,200	150
26	700	1,200	200



### SC 스테인레스 분전함 옥외 방수용 BOX 1.2T

(단위 : mm)

모델	가로(W)	세로(H)	깊이(D)
1	300	400	150
2	400	500	150
3	400	500	200
4	500	600	150
5	500	600	200
6	500	700	150
7	500	700	200
8	600	600	150
9	600	700	150
10	600	700	200
11	600	800	150
12	600	800	200
13	600	900	150
14	600	900	200
15	600	1000	150
16	600	1000	200
17	700	800	150
18	700	800	200
19	700	900	200
20	700	1000	200
21	700	1000	250
22	700	1200	200
23	700	1200	250
24	800	1200	250

No-1



노출함 (STEEL)	BOX 규격	W400×H500×D150
	극수	2P
	메인(MCCB)	2P 50A 14KA(1개)
	분기회로(ELB)	2P 20A 2.5KA(10개)

No-6




노출함 (STEEL)	BOX 규격	W500×H600×D150
	극수	4P
	메인(MCCB)	4P 50A 14KA(1개)
	분기회로(ELB)	3P 30A 5KA(2개) 2P 20A 2.5KA(10개)

No-2




노출함 (STEEL)	BOX 규격	W500×H600×D150
	극수	2P
	메인(MCCB)	2P 75A 14KA(1개)
	분기회로(ELB)	2P 30A 5KA(2개) 2P 20A 2.5KA(8개)

No-7




노출함 (STEEL)	BOX 규격	W500×H600×D150
	극수	4P
	메인(MCCB)	4P 75A 14KA(1개)
	분기회로(MCCB)	3P 30A 5KA(2개)
분기회로(ELB)	2P 30A 5KA(2개) 2P 20A 2.5KA(8개)	

No-3



노출함 (STEEL)	BOX 규격	W500×H600×D150
	극수	4P
	메인(MCCB)	4P 50A 14KA(1개)
	분기회로(ELB)	2P 20A 2.5KA(14개)

No-8




노출함 (STEEL)	BOX 규격	W600×H600×D150
	극수	4P
	메인(MCCB)	4P 50A 14KA(1개)
	분기회로(ELB)	4P 30A 14KA(2개) 2P 20A 2.5KA(8개)

No-4




노출함 (STEEL)	BOX 규격	W500×H600×D150
	극수	4P
	메인(MCCB)	4P 50A 14KA(1개)
	분기회로(ELB)	2P 30A 5KA(2개) 2P 20A 2.5KA(8개)

No-9




노출함 (STEEL)	BOX 규격	W600×700×D150
	극수	4P
	메인(MCCB)	4P 100A 14KA(1개)
	분기회로(MCCB)	4P 30A 14KA(1개)
분기회로(ELB)	3P 30A 5KA(2개) 2P 20A 2.5KA(10개)	

No-5



노출함 (STEEL)	BOX 규격	W500×H600×D150
	극수	4P
	메인(MCCB)	4P 50A 14KA(1개)
	분기회로(ELB)	3P 30A 5KA(2개) 2P 20A 2.5KA(6개)

No-10



노출함 (STEEL)	BOX 규격	W600×H700×D150
	극수	4P
	메인(MCCB)	4P 75A 14KA(1개)
	분기회로(ELB)	4P 30A 14KA(2개) 2P 20A 2.5KA(14개)